

**Amendments to the Claims**

The listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims**

1. (original) A mortice lock including a deadbolt retained within a lock case and movable between an unlocking position wherein the deadbolt is disposed within the lock case, and a locking position in which it extends outwardly from a fore-end thereof, and a driving mechanism rotatable about an axis transverse to the direction of movement of the deadbolt and having a cam which connects with and moves the deadbolt between said positions;  
characterised by at least one contact member mounted on and movable with respect to the deadbolt between a first position in which the contact member maintains contact with the driving member to effect a full throw of the deadbolt in one direction, and a second position to enable a full throw of the deadbolt in an opposite direction.
2. (original) A mortice lock according to Claim 1, wherein the driving member is a key.
3. (original) A mortice lock according to Claim 1, wherein the driving member is a cylinder cam.
4. (original) A mortice lock according to Claim 1, wherein the driving member is a key cam associated with multiple levers.
5. (currently amended) A mortice lock according to Claim 1, including two contact members mounted on the deadbolt, one of which maintains contact with the driving member throughout the movement of the deadbolt into the locking

position, the other maintaining contact with the driving member throughout the movement of the deadbolt into the unlocking position.

6. (currently amended) A mortice lock according to Claim 1, wherein the or each contact member is movable into a position in which it prevents movement of the deadbolt.
7. (currently amended) A mortice lock according to Claim 1, wherein the or each contact member has a cam follower residing in a track in the lock case, the track being formed to effect movement of the contact member between its first and second positions.
8. (currently amended) A mortice lock according to Claim 1, wherein the deadbolt, in its locking position, extends from the fore-end of the lock case by at least 20mm.
9. (currently amended) A mortice lock according to Claim 1, in which the or each contact member is slidably mounted on the deadbolt and has a pin which permits limited vertical movement within a slot in the deadbolt.
10. (currently amended) A mortice lock according to Claim 1, including a dummy lever which is adapted to move horizontally within the lock case along with the deadbolt and has a pin which rides in a horizontal track in the lock case.
11. (currently amended) A mortice lock according to Claim 1, including a spring located to urge the or each contact member in a downwards direction in relation to the deadbolt during operation of the lock.

12. (currently amended) A mortice lock according to Claim 1, wherein the or each contact member is rotatably movable with respect to the deadbolt to extend the range of contact between the driving member and the deadbolt.
13. (currently amended) A mortice lock according to Claim 1, including at least one wedge mounted in the casing and contacted by the or each contact member thus to effect movement thereof relative the deadbolt.